

## VAF1500A

Americ Confined Space Ventilator



Blade Color :	Black	Housing Color :	Yellow
Blade Material :	Polypropylene	Housing Material :	Polyethylene
CFM (free air) :	880	Maximum Duct Length (feet) :	50
CFM (with 25' of duct) :	600	Maximum Static Pressure (in. H2O) :	1.5
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Nameplate Amps :	2.5
CFM Range (Free Air) :	<1000	Number of Wings :	5
CFM/Watt (free Air) :	4.6	Oscillating :	No
Component Certifications :	Motor - UL/CSA	Performance Test No. :	500
Cord :	Included - Wired	Phase :	1
Cord Length (feet) :	20	Power (hp) :	1/4
Country of Origin :	US	Power (Voltage & Phase) :	115 Single Phase
Diameter (inches) :	8	Product Certifications :	cULus
Distinguishing Feature :	Suitable with Ducting	Product Color :	Yellow
Drive Type :	Direct	Product Dimensions (L x W x H inches) :	18.5" x 18.5" x 12.5"
Fixed or Portable :	Portable	Product Weight (pounds) :	18
Frequency (Hz) :	60	Speeds :	1
Guard Color :	Black	Switch :	On product
Guard Material & Coating :	Powder Coated Steel	Voltage :	115
Guard Spacing (inches) :	1/2 OSHA		