

**VF30**  
30" Misting Fan



Blade Color :	White	Guard Material & Coating :	Powder Coated Steel
Blade Material :	Aluminum	Guard Spacing (inches) :	1/2 OSHA
CFM (@0.05") :	5800	Housing Color :	White
CFM (free air) :	6420	Nameplate Amps :	2.4
CFM (high) :	6420	Number of Wings :	3
CFM (low) :	4890	On Board Reservoir :	No
CFM (medium) :	5620	Operating Temperature (high) :	40C
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Operating Temperature (low) :	0C
CFM Range (Free Air) :	5001 - 10000	Oscillating :	Yes
CFM/Watt (free Air) :	32.3	Performance Test No. :	399
Cooling Capacity (1000 btu) :	108	Phase :	1
Cord :	Included - Wired	Power (hp) :	1/4
Cord Length (feet) :	25	Power (Voltage & Phase) :	115 Single Phase
Country of Origin :	US	Product Certifications :	cULus
Diameter (inches) :	30	Product Color :	White
Distinguishing Feature :	Cools Air via Evaporative Cooling	Product Weight (pounds) :	164
Drive Type :	Direct	Speed Control Compatible :	No
Fixed or Portable :	Portable	Speeds :	3
Frequency (Hz) :	60	Switch :	On product
Guard Color :	White	Voltage :	115